



2 HOSES + 1 COUPLING = A TOTAL HYDRAULIC SOLUTION

Why not simplify your product lineup?

Kurt Hydraulics can handle the widest range of hydraulic applications and pressures with only 2 hose models and 1 coupling series. Carrying less inventory and covering more solutions makes business easier for everyone—from distributors to installers to customers. The combination of Kurt E-Z Bend Hose + Kurt Tuff Hose + Kurt W-Series Couplings is your best bet for covering the most common hydraulic hose and coupling applications. If you want to stock just 3 product lines check out this solution.



Give us a call today, we'll be happy to earn your business and trust - TOLL FREE 1-866-257-7995
hydraulicsales@kurt.com | kurthydraulics.com



KURT TUFF HYDRAULIC HOSE

Recommended for: High pressure hydraulic oil lines

Tube: Oil resistant synthetic rubber

Reinforcement: Two high tensile steel wire braid

Cover: 10X abrasion, ozone and weather resistant synthetic rubber meets flame resistant MSHA designation

Temperature Range: -40°F to +212°F (+250°F Max)

Features:

- Extra-flexible, Light-weight, very-high pressure braided hose
- Abrasion resistant tuff cover
- Impulse tested up to 1,000,000 cycles
- Uses W Series couplings



W STYLE COUPLINGS

Couplings can be used on:

- 1 wire braided hose (R1, R17)
- 2 wire braided hose (R2, R16, R17, KT)
- All size R12 non-skive (6-32)
- 4SH non-skive (12-24)
- Industrial hose
- Compatible with many crimp systems



KURT E-Z BEND 4SK HYDRAULIC HOSE

Recommended for: High pressure hydraulic oil lines

Tube: Oil resistant synthetic rubber

Reinforcement: Four spiral layers of high tensile steel wire braid

Cover: Abrasion, ozone and weather resistant synthetic rubber meets flame resistant MSHA designation

Temperature Range: -40°F to +212°F

Features:

- More pliable and less force required to bend
- Uses W Series couplings



▶ **Talk to a sales rep today to learn about Kurt's 2 + 1 Total Solution**

KURT TUFF HYDRAULIC HOSE					
Part Number	Hose I.D. [in.]	Hose O.D. [in.]	Rated W.P. [psi]	Min. Burst [psi]	Min. Bend [in.]
KT-04	1/4	0.58	6,500	26,000	2
KT-06	3/8	0.69	5,500	22,000	3
KT-08	1/2	0.81	5,000	20,000	3.5
KT-10	5/8	0.93	4,250	17,000	5
KT-12	3/4	1.09	4,000	16,000	6.5
KT-16	1	1.40	3,000	12,000	8
KURT E-Z BEND 4SK HYDRAULIC HOSE					
Part Number	Hose I.D. [in.]	Hose O.D. [in.]	Rated W.P. [psi]	Min. Burst [psi]	Min. Bend [in.]
4SK-10	5/8	1.07	6,000	24,000	4
4SK-12	3/4	1.27	6,000	24,000	4.70
4SK-16	1	1.52	5,500	22,000	5.90
4SK-20	1-1/4	1.79	5,000	20,000	9