


KURT HYDRAULIC GL TRUCK HOSE AND COUPLINGS

Kurt GL Truck Hose



Recommended for: DOT approved. Used for high temperature truck and bus applications, diesel fuel, gasoline, hot oil, air brakes and hydraulics.

Tube: Black, synthetic rubber

Reinforcement: Textile inner braid and a braid of higher tensile steel wire

Cover: Oil and mildew resistant black textile braid

Temperature range: -40°F to +300°F

Skiving Required: No

Part Number	Hose I.D. (in.)	Hose O.D. (in.)	Rated W.P. (psi)	Min. Burst (psi)	Min. Bend (in.)	Weight (Lb/100 Ft)	Coupling Series
GL-04	3/16	.49	1500	6000	3	11	STD-R5, Reusable
GL-05	1/4	.55	1500	6000	3.4	13	STD-R5, Reusable
GL-06	5/16	.62	1500	6000	4	15	STD-R5, Reusable
GL-08	13/32	.74	1250	5000	4.6	19	STD-R5, Reusable
GL-10	1/2	.83	1000	4000	5.5	21	STD-R5, Reusable
GL-12	5/8	.96	750	3000	6.5	26	STD-R5, Reusable
GL-16	7/8	1.21	400	1600	7.4	34	STD-R5, Reusable
R5-20	1-1/8	1.49	300	1250	9	45	STD-R5, Reusable



R5 Couplings

- All sizes 4-32
- Slide on crimp coupling (non reusable)
- Easy to install
- Large selection of ends available
- Price competitive



Braided Hose Couplings

- Kurt's first design
- Compatible with many crimpers
- Can be used on 1 & 2 wire braided hose
- Can be used on thermoplastic hose
- Great for industrial hose



Give us a call today, we'll be happy to earn your business and trust - TOLL FREE 1-866-257-7995
hydraulicsales@kurt.com | kurthydraulics.com