



# FULL LINE OF PRESSURE WASH HOSE & COUPLINGS

## 1SN & 2SN Pressure Wash Hose

**Recommended for:** Medium pressure wash applications including industrial pressure washing, industrial cleaning, car wash systems, carpet cleaning systems and more.

**Tube:** Water resistant synthetic rubber

**Reinforcement:** One or two high tensile steel wire braid.

**Cover:** Abrasion, ozone and weather resistant synthetic rubber. Black & blue covers available.

**Temperature Range:** -40°F to +300°F

Part Number	Hose I.D. (in.)	Hose O.D. (in.)	Rated W.P. (psi)	Min. Burst (psi)	Min. Bend (in.)
PW-04	1/4	0.50	4,000	8,000	1.5
PWB-04	1/4	0.50	4,000	8,000	1.5
PW-06	3/8	0.63	4,000	8,000	3.0
PWB-06	3/8	0.63	4,000	8,000	3.0
PW2-06	3/8	0.68	6,000	12,000	3.5
PW2B-06	3/8	0.68	6,000	12,000	3.5
PW2-08	1/2	0.84	6,000	12,000	7
PW2B-08	1/2	0.84	6,000	12,000	7

## KURT K2 Couplings for pressure wash:

- Sizes 4-10
- Reduced size Bite-Wire shell for good compact hose fit
- Excellent performing coupling on new compact hoses
- Price competitive / Large selection available

## KURT Karcher Female Swivel for pressure wash:

- 1/4" and 3/8" ID available
- Easy twist-on and twist-off



Give us a call today, we'll be happy to earn your business and trust - TOLL FREE 1-866-257-7995  
[hydraulicsales@kurt.com](mailto:hydraulicsales@kurt.com) | [kurthydraulics.com](http://kurthydraulics.com)